

**SPECIFICATIONS**

HEATING -24700 BTU/H (AT 150°F T.D)  
 AIR FLOW -295 CFM  
 CURRENT -12 AMPS (AT 12V)  
 WEIGHT -9 LBS.

3-SPEED MOTOR


**NOTE:**

CASING MADE OF 18GA. CRS. AND FINISHED IN BLACK SEMI-GLOSS EPOXY POWDER COAT.

ALL MOTOR WIRES: 16GA GPT (60°)  
 300 mm LONG  
 TERMINALS: 4x .25 TAB TERMINAL  
 AMP# 42460-2

6	2	28-0013	SNAP IN PLUG
5D	2	25-0022	CLIP
5C	1	25-2641	MOTOR ASSY. 12V
5B	2	25-0021	BLOWER WHEEL
5A	1	25-0017	BLOWER HOUSING
5	1	15-0503	BLOWER 12V
4	1	22-0024	HEATER COIL
3	2	24-0012	BRACKET
2	1	24-0008	COVER
1	1	24-0009	CASING

7	REVISED AS PER ECN# 6680	MAY 07/08	AK	TOLERANCE UNLESS OTHERWISE SPECIFIED
6	REVISED AS PER ECN# 4527	AUG 11/06	IK	
5	REVISED AS PER ECN# 3875	AUG 12/03	IK	
4	REVISED AS PER ECN# 3538	JAN 27/03	OP	
SYM	DESCRIPTION	DATE	BY	
	REVISION			



CHECK BY: MM DATE: May 07, 08

**MCC** Mobile Climate Control Inc.  
 Toronto - Ontario - Canada

SYM	PCS	PART NO.	DESCRIPTION	SCALE: NTS	BY: CP
		12-0203	HEATER 12V	DATE: APR 14, 1997	
				DWG: P3-4970	REV: 7